



UNI BATTEN SERIES

IP20 WITH SENSOR & REMOTE CONTROL

The Uni IP20 Sensor Batten is built around a philosophy of delivering ease of installation with high efficiency.

The batten's built in dual motion & lux sensor is easily controlled by the Emerald Planet **Universal Remote Control** (sold separately). The handheld remote switches the sensor on & off and adjusts hold time, stand by periods and stand by dimming levels. The remote control also includes 4 pre-set program options to choose from. You have the choice to set your own preferences or select from one of the pre-set arrangements.

FEATURES

- Traditional batten profile
- Surface mountable or suspendable
- No external junction box required
- Broad 120° beam angle
- Available with built-in sensor
- IK08 rating
- Dual motion & lux sensor



Remote control EP-UNIV-R

SPECIFICATIONS

POWER FACTOR	>0.9	MODEL NUMBER	CCT	DIMENSIONS	WATT	LCP	LUMENS	EFFICACY
CRI	>80	EP-UNIG2-S1220-25	5000K	71x76x1221mm	25	24.23	3609	148m/W
BEAM ANGLE	120°	EP-UNIG3-S1220-15	5000K	71x76x1221mm	15	14.97	2515	168m/W
IP RATING	20	EP-UNIG3-S1220-15	5700K	71x76x1221mm	15	14.97	2515	168m/W
LIFETIME (L70)	>60,000hrs	EP-UNI-S1220-25	5000K	71x76x1221mm	25	24.76	3383	137lm/W
WARRANTY	5 Years	EP-UNI-S1220-25	5700K	71x76x1221mm	25	24.76	3383	137lm/W

